

TECHNICAL SPECIFICATIONS OF LADIES SAFETY SHOES (DERBY)

Description	Specifications
Brand	JCB
	LADIES DERBY Safety Shoe DUCHESS
<i>Operative Standard</i>	<i>Meets IS 15298:2002 Part I & II & EN 20345</i>
<i>Description</i>	Black 4 Eyelet safety shoe, Single Density Slip resistant Direct Injected PU Sole. Nail less. As per design A (4.2 of IS 15298 part 1)
SIZES	UK (Range 2-8)
Height & size of shoe	Less than 113 mm for size 8 (+/- 5 mm)
Color	Black
Marking	As per IS 15298 (Part 2):2002 Clause 6 or EN 20345 CE marking
	ISI Marked
Electrical Properties	Antistatic. Resistance between 100 Kilo Ohms & 1000 mega ohms
Upper leather	Buff Grain Textured Leather
Upper I thickness	As per <i>S 15298:2002 Part I & II & EN 20345</i>
Vamp lining	Non Woven Polyester
Tongue & Collar	Padded Leather
Lining other than vamp	Grey Mesh Medium Hole
Socks	Full EVA padded
Insole	Non Woven Antistatic
Out Sole	PU Single density L03 Mould
Sole fixation	Direct injection process on DESMA Machines
Other	Nail less construction
HEEL STIFFNER	Molded stiffener for additional support.
Sole Cleated Area	As per 6.4.1 of IS 15298 (Part 2)
Cleat Height (thickness)	As per 6.4.3 of IS 15298 (Part 2)
Sole Thickness cleated outsole	As per 6.4.2 of IS 15298 (Part 2)
Sole Abrasion Resistance	As per 5.8.3 of IS 15298 (Part 2)
Sole Flexing Resistance	As per 5.8.4 of IS 15298 (Part 2)
Bond Strength	As per 5.3.1.2 of IS 15298 (Part 2)
Steel Toecap	Rust resistant Epoxy Coated EN 12568 marked imported with Polymer comfort strip. Level of protection 200 joules. Also protect against compression injury
Padding under steel toe	Polymer Strip for comfort
Thread	White Nylon 20 and 40 No.
Eye let	4 Rust Resistant Metal Eyelets
Lace	Round Double Colored Nylon
MARKING	CE or as per IS 15298 Part II Antistatic
SUITABLE FOR	ENGINEERING, PETROCHEMICAL & CONSTRUCTION
Branding on Upper	JCB two colored Polymer Label on outer side
Branding on Tongue	JCB two colored Polymer Label on Tongue
Branding on Socks	JCB Fabric woven label on heel area of the socks



IS 15298

(PART 2)
CM/L-4867488



Sole Licensee in India
RAHMAN INDUSTRIES LTD

310, Krishna Towers, 15/63, Civil Lines,
KANPUR 208001 INDIA

PH: + 91 512 2331072

FAX: + 91 512 2330601 & 2464357

MOB: 91 9336811103 & 91 9336110112

kt@rahman-group.com

www.jcbfootwear.in